WATER QUALITY / DATA SHEET

SS312-01-ETH-2

Suspended Solids Transmitter

Self-cleaning optical measurement of suspended solids and sludge concentration with Ethernet data upload.



Overview

- Measures suspended inorganic and organic solids, sediment and microorganisms in water.
- Optical absorption measurement requires no chemical reagents.
- Sends readings over Ethernet to a cloud platform or customer server for centralized monitoring.

Maximum Range	Resolution	Power Supply	Upload
0–20000 mg/L	0.1 mg/L	DC 12–30 V	Ethernet

Key Advantages

- Integrated self-cleaning system reduces biofouling.
- Modulated light reduces visible-light interference.
- Automatic temperature compensation.
- 2 s acquisition; configurable upload interval.
- RJ45 interface; static IP, DHCP and DNS support.

Application Scenarios

- Water treatment.
- Aquaculture.
- Environmental monitoring.
- Online sludge concentration monitoring.

SYSTEM DATA

Technical Specifications

Item	Specification
Model	SS312-01-ETH-2
Measurement principle	Optical absorption
Range options	0–20000 / 0–5000 / 0–1000 / 0–200 mg/L; select one
Measurement error	±5% FS; depends on sludge homogeneity
Resolution	0.1 mg/L
Response time	≤30 s
Supply voltage	DC 12–30 V
Power consumption	1.4 W normal; 4.7 W during self-cleaning
Data upload	Ethernet; RJ45; TCP upload; static IP or DHCP; gateway and DNS support
Probe operating temperature	0–40 °C
Housing environment	−40 to +60 °C; 0–95% RH, non-condensing
Ingress protection	Probe: IP68; transmitter housing: IP65

Item	Specification
Flow velocity	<3 m/s
Probe pressure limit	<0.1 MPa
Data acquisition interval	2 s
Data upload interval	30 s default; 1–60000 s in specification table; configuration section states 1–65535 s
Probe cable	5 m standard; customizable
Housing material	Corrosion-resistant plastic and stainless steel
Maintenance / calibration interval	3 months recommended
Self-cleaning system service life	18 months; dynamic seal replacement required after continuous use
Housing dimensions	117 × 87 × 43 mm maximum
Probe dimensions / thread	247 mm dimension shown; 227 mm body dimension; Ø50 mm; NPT 3/4

MEASUREMENT DATA


Calibration and Range Selection

Calibration condition	Requirement
Factory reference	Kaolin standard, selected for the optical transmission measurement method.
Site calibration	Use a standard prepared from sludge representative of the installation environment to ensure homogeneity and appropriate concentration calibration.

Ordering model: SS312-01-ETH-2. Specify the required 20000, 5000, 1000 or 200 mg/L full-scale range and cable length. The wall-mounted housing and self-cleaning probe form the Ethernet monitoring system.

MECHANICAL DATA

Dimensions and Installation



Dimensions in millimetres: probe Ø50 mm, 247 mm and 227 mm dimensions as shown; NPT 3/4 thread. Housing: 117 × 87 × 43 mm maximum. Wall mounting spacing: 105 mm; use Ø5 mm holes with the supplied plugs and screws.

Horizontal probe placement is preferred to reduce sediment accumulation. Install in bubble-free water at a depth no greater than 2 m and at least 30 cm below the lowest water level. Prevent the suspended probe from striking walls or structures; secure it where flow is strong. Route the cable through a waterproof support pipe and attach using the NPT 3/4 thread.

ELECTRICAL CONNECTION

Power Connection and Start Up

Connection	Instruction
Supply voltage	DC 12–30 V; supplied adapter: 12 V
Start up	Connect the adapter to the power input, then energize
Data availability	Wait 1–3 minutes, then view readings at the platform or receiving server

COMMUNICATION DATA

Ethernet Configuration and Data Upload

Connect the RJ45 Ethernet port to the network. Use the supplied Android configuration app with Bluetooth enabled. Scan for ETHM followed by the device address, connect with default password 12345678, read the required parameters, edit settings and send them to the device. Read back to verify changes and use real-time data to check readings.

Set the receiving server public IP address or domain and matching listening port (default 8020). Select static IP or DHCP; for static IP, set the IP address, subnet mask and gateway. Upload interval defaults to 30 s; the configuration section gives 1–65535 s, while the specification table gives 1–60000 s. Confirm the supported upper limit before use. The unique 8-digit device address cannot be changed. Operation password: 1–8 numeric digits, default 12345678.

Monitoring platforms: local software runs on a customer PC or server; the cloud option needs no customer server. Both offer web monitoring, limit alarms, email alerts, history export and permission management. Local SMS alerts require an additional SMS modem.

CALIBRATION & MAINTENANCE

Self Cleaning and Probe Maintenance

Inspect the measurement windows for deposits and scale. Rinse with tap water and wipe with a soft damp cloth; household detergent in water may be used for stubborn deposits. Do not touch or scratch the windows. Keep bubbles off the probe and measurement windows during measurement and calibration. Protect the probe from impact, direct sunlight, cable tension and mechanical stress.

Check the cleaning brush regularly for correct operation and damage. Do not force the brush shaft to rotate. After 18 months of continuous self-cleaning use, return the device for dynamic seal replacement; adjust the service interval to actual cleaning frequency. Calibrate before each use and approximately every 3 months for long-term operation, adjusting for fouling and chemical deposits. Check window cleanliness if readings are high, low or persistently unstable.

Do not use this device as a safety device or emergency stop device, or in applications where equipment failure could cause personal injury. Read the operating instructions before installation, use or servicing.

Package contents: one self-cleaning suspended solids transmitter, 5 m cable, one 12 V adapter, two expansion plugs, two self-tapping screws, Ethernet cable, nylon protective net, certificate and warranty card. Warranty: 12 months for verified defects in materials or workmanship under normal use and maintenance.

CONTACT / SUPPORT

SpeSense Technologies Inc.
Add: No. 9 Yuhe Road, Guitang Subdistrict, Yuhua District, Changsha City
Tel: +86-15386478166
Email: info@spesense.com
Web: www.spesense.com

WHATSAPP WECHAT

WhatsApp / WeChat